



QUZHOU QFREON CHEMICAL CO.,LTD. MSDS-R507

MATERIAL SAFETY DATA SHEET

(REFRIGERANT GAS R507)

1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Product Name : Pentafluoroethane and 1,1,1-Trifluoroethane

Synonyms: R-507

Formula: $\text{CHF}_2\text{CF}_3/\text{CH}_3\text{CF}_3$

MANUFACTURER:

Quzhou Qfreon Chemical Co.,Ltd.

Add: No.1, Hehua Road, Economic Development Zone, Quzhou City, Zhejiang
Province, China

TEL: 86-18605701216 FAX: 86-570-3662230 www.qfreon-chemical.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT NAME | CAS NUMBER | WEIGHT % |
|----------------------------------|------------|----------|
| Pentafluoroethane (HFC-125) | 354-33-6 | 50 |
| 1,1,1-Trifluoroethane (HFC-143a) | 420-46-2 | 50 |

3. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Gas at ambient temperatures

Color/Colour: Colorless/colourless

Odor/Odour: Slight, ether-like.

Molecular Weight: 98.8 average

Boiling Point(1013 mbars): - 46.9 °C

PH: Neutra

Vapor Pressure: 184.9 psia (25°C)

4. FIRE FIGHTING MEASURES

SKIN: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with



QUZHOU QFREON CHEMICAL CO.,LTD. MSDS-R507

a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

INHALATION: Immediately remove to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention. Do not give epinephrine (adrenaline).

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

ADVICE TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5. HAZARDS IDENTIFICATION

Hazardous Classification: Class 2.2 Compressed Gas and Non-combustible Gas

Primary Routes of Entry: Inhalation, Skin Contact, Eyes

Emergency Overview: Inhalation of high concentrations of vapor is harmful and may cause heart irregularities, unconsciousness, or death. Intentional misuse or deliberate inhalation may cause death without warning. Vapor reduces oxygen available for breathing and is heavier than air. Liquid contact can cause frostbite.

Potential Health Hazards:

Skin: Skin contact may cause frostbite from exposure to the liquid.

Eyes: Irritant. Liquid contact will irritate and may cause conjunctivitis.

Inhalation: Inhalation may include nonspecific discomfort, such as nausea, headache, or weakness; or temporary nervous system depression with anesthetic effects such as dizziness, headache, confusion, incoordination, and loss of consciousness.

Ingestion : Discomfort due to volatility would be expected.

6. FIRST AID MEASURES

Eyes: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite, water should not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

Skin: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

Inhalation: Immediately remove patient to fresh air. If breathing has stopped, give artificial respiration.



QUZHOU QFREON CHEMICAL CO.,LTD. MSDS-R507

Use oxygen as required, provided a qualified operator is available. Get medical attention immediately. DO NOT give epinephrine(adrenaline).

Ingestion: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. DO NOT induce vomiting unless instructed to do so by a physician.

Advice to Physician: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

7. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Immediately contact emergency personnel. Use suitable protective equipment. Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.

Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for Cleaning-up: Evaporates.

In Case of Spill or Other Release: (Always wear recommended personal protective equipment.) Evacuate unprotected personnel. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return until air has been tested and determined safe, including low lying areas.

8. HANDLING AND STORAGE

Handling: Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders. Follow standard safety precautions for handling and use of compressed gas cylinders. R-507 should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52°C.

9. EXPOSURE CONTROLS/PERSONAL PROTECTION

Authorized Limit Values:

| INGREDIENT NAME | ACGIH TLV | OSHA PEL | OTHER LIMIT |
|-------------------|-----------|----------|--|
| Pentafluoroethane | None | None | 1000 ppm ,4900 mg/m ³ TWA (8hr) |



QUZHOU QFREON CHEMICAL CO.,LTD. MSDS-R507

1,1,1-Trifluoroethane None None 1000 ppm TWA (8hr)

= Workplace Environmental Exposure Level (AIHA)

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Respiratory Protection: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hand Protection: Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling.

10. STABILITY AND REACTIVITY

Stability: The product is stable. Do not mix with oxygen or air above atmospheric pressure. Any source of high temperatures, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

Incompatibility With Other Materials: Avoid contact with strong alkali or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers since they may react with or accelerate decomposition of this material.

Hazardous Decomposition Products: Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and possibly carbonyl fluoride. These materials are toxic and irritating. Contact should be avoided.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Immediate (Acute) Effects:

Pentafluoroethane (R-125): LC₅₀ : 4 hr. (rat) - > 800,000 ppm

Cardiac Sensitization threshold (dog) >75,000 ppm

Trifluoroethane (R-143a): LC₅₀ : 4hr. (rat) -> 540,000 ppm

Cardiac Sensitization threshold (dog) > 250,000 ppm

Delayed (Subchronic and Chronic) Effects:



QUZHOU QFREON CHEMICAL CO.,LTD. MSDS-R507

Pentafluoroethane (R-125): Teratogenic NOEL (rat and rabbit) - 50,000 ppm *Trifluoroethane (R-143a):

Subchronic inhalation (rat) NOEL - $\geq 50,000$ ppm Chronic NOEL - 10,000 ppm

Teratogenic NOEL (rat) - 40,000 ppm

Subchronic inhalation (rat) NOEL - 40,000 ppm

Other Data:

Pentafluoroethane (R-125): Not active in four genetic studies

Trifluoroethane (R-143a): Not active in two genetic studies

Toxicity to reproduction: Did not show mutagenic or teratogenic effects in animal experiments.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

The compound is very low to slightly toxic.

Trifluoroethane (R-143a): 96-hour LC_{50} , Rainbow trout: >40 mg/L

Degradability (BOD):

R-507 is a gas at room temperature; therefore, it is unlikely to remain in water.

Octanol Water Partition Coefficient: $\log P_{ow} = 1.48$ (R-125)

13. DISPOSAL CONSIDERATIONS

Nature of the Waste: Not a RCRA hazardous waste.

Waste Treatment: Waste from residues / unused products: Can be used after re-conditioning.

Product removed from the cylinder must be disposed of in accordance with appropriate National and local regulation. Return cylinders with residual product to the supplier.

14. TRANSPORTATION INFORMATION

Proper Shipping Name: Liquefied gas, n.o.s., (Pentafluoroethane, 1,1,1-Trifluoroethane)

HAZARD CLASS: 2.2

UN No. : 3163

Primary Label: Nonflammable Gas

15. OTHER INFORMATION

The information given correspond to the current state of our knowledge and experience of the product,



QUZHOU QFREON CHEMICAL CO.,LTD. MSDS-R507

and is not exhaustive. This applies to product that confirms to the specification, unless otherwise stated. In the case of combinations and mixtures one must make that no new dangers can arise. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and environment.

Responsibility for MSDS: MSDS Coordinator

Quzhou Qfreon Chemical Co.,Ltd.

Add: No.1, Hehua Road, Economic Development Zone, Quzhou City, Zhejiang
Province, China

TEL: 86-570-3662230 FAX: 86-570-3662230 www.qfreon.cn

Indicates updated section.

End of MSDS